

Aftercare & Maintenance

Galvanized Steel Components

Citysquared recommend the cleaning process is undertaken approximately every 3 months, depending on the installation environment, to maintain optimum appearance.

<p>1.0</p> <p>For routine cleaning, use a soft cloth, dampened with clean, <u>warm</u> water, then dry with a soft cloth.</p> <p>Remove water deposits with a clean cloth.</p>	<p>2.0</p> <p>For a routine deep clean, use a mild non-alkaline detergent and apply with a soft cloth.</p> <p>Clean down with warm water to remove any detergent residue from the component surface and dry with a clean cloth.</p>
<p>3.0</p> <p>For more stubborn stains or discolourations, apply a mild non-abrasive proprietary galvanized steel cleaner to the component surface.</p> <p>Apply with a lint-free cloth or soft brush, as per the manufacturer's directions. Rub gently using a circular motion.</p> <p>Observe the manufacturer's application guidelines. With any irritant goggles and gloves should be worn.</p>	<p>4.0</p> <p>To remove hard water stains, a solution of equal parts white distilled vinegar and water can be used.</p> <p>To further protect the surface, apply a very small amount of clear wax or metal polish to the rinsed and dried surface using a soft cloth. Use another clean lint-free cloth to gently buff the surface.</p>
<p>Exterior Installations</p> <p>Pressure washers may be used to clean down any items installed in an exterior environment. Care should be taken to wipe down the items thoroughly after pressure washing to remove any debris deposited on the items during this process. Any residue left on the galvanized steel can cause contamination. Do not use a detergent in conjunction with the pressure washer; some detergents can create an adverse reaction with the Zinc finish.</p>	