Aftercare and Maintenance Solid Timber Components with a Danish Oil Finish

To ensure a quality product, *Citysquared* use only materials that meet the highest standards for durability and strength. With regular care and maintenance, your furniture will provide years of superior performance and satisfaction.

Citysquared recommend this process is undertaken approximately every 3 to 6 months, depending on the installation environment and number of previous coats, to maintain optimum appearance.



1.0 Clean component with a mild proprietary timber cleaning agent.

Scrubbing may be required where build ups have occurred. Rinse thoroughly with water, use a lint free cloth and wring out well. Buff dry.

For stubborn stains use a bleach solution or oxalic acid as per suppliers' instructions. Goggles & gloves must be worn when using any irritant.



2.0

Lightly sand using grade 180 paper to denib. Ensure a dust

Wrapping the sand paper around a soft block will keep the surface even.

Remove all dust from surface with a lint free cloth and white spirit, or tack cloth, prior to stage 3.0



3.0

Using a brush, apply a thin coat of oil to the component surface. Apply along the grain.

Allow 15 to 20 minutes to absorb then remove any excess with a lint free cloth.



Repeat the process after approximately 1 hour.

Allow to dry, observing the oil manufacturers' drying time.



Aftercare and Maintenance Solid Timber Components with a Danish Oil Finish





Typical Before and After Results

Materials and Tools

- Proprietary timber cleaning agent
- Water (approx 1L per bench)
- White Spirit
- Danish Oil
- •Scrubbing Brush nylon bristles
- •Scraper (to remove chewing gum/foreign matter)
- 180/240 grit sandpaper
- •Sanding Block
- •Paint Kettle (to decant oil)
- Paint Brush
- Decorators rags
- Hazard tape
- Bollards

