

Aftercare & Maintenance

Stainless Steel Components

Citysquared recommend the cleaning process is undertaken approximately every 3 months, depending on the installation environment, to maintain optimum appearance.

<p>1.0</p> <p>For routine cleaning, use a soft cloth, dampened with clean, <u>warm</u> water, then dry with a soft cloth.</p> <p>Do not allow water beads to dry on the surface.</p>	<p>2.0</p> <p>For a routine deep clean, use a mild detergent and apply with a soft cloth.</p> <p>Clean down with warm water to remove any residue from the detergent from the component surface and dry with a clean cloth.</p>
<p>3.0</p> <p>For more stubborn stains or discolourations, apply a mild non-abrasive, proprietary stainless steel cleaner to the component surface.</p> <p>(Example appropriate products would be: 3M Stainless Steel Cleaner and Polish, De-Solve – It Stainless Steel Cleaner & Method Stainless Steel Spray).</p> <p>Rub gently in direction of the polish lines. Apply with a soft cloth. Do not use an abrasive cloth.</p> <p>Observe the manufacturers application guidelines. With any irritant goggles and gloves should be worn.</p>	<p>4.0</p> <p>To create a lustre, apply a very small amount of clear oil to a soft cloth and wipe over the component surface.</p>
<p>Exterior Installations</p> <p>Pressure washers may be used to clean down any items installed in an exterior environment. Care should be taken to wipe down the items thoroughly after pressure washing to remove any debris deposited on the items during this process. Any residue left on the stainless steel can cause contamination. Do not use a detergent in conjunction with the pressure washer, some detergents can create an adverse reaction with the stainless steel.</p>	