

## Aftercare & Maintenance

### Polyester Powder Coated Steel Components

Citysquared recommend the cleaning process is undertaken approximately every 3 months, depending on the installation environment, to maintain optimum appearance. Periodic touch up painting may be required.

<p>1.0</p> <p>Clean component surface with a mild detergent and warm water. Check detergent is non-abrasive by testing on an inconspicuous area, to ensure that gloss levels/finishes are not damaged.</p> <p>Use a lint free cloth and wring out well.</p> <p>Change the water frequently.</p> <p>Dry with a clean soft cloth.</p>	<p>2.0</p> <p>To repair scuffs and light scratches, buff the area with a fine Scotch-Brite™ pad to flatten the paint surface.</p> <p>Paint over the area using a brush appropriate in size to the damage.</p> <p>Use enough paint to give an even coverage.</p> <p>Paint may be sourced from your local paint supplier, or alternatively Citysquared are happy to source this for you.</p>
<p>3.0</p> <p>To repaint larger areas a gloss roller may be more appropriate.</p> <p>Use enough paint to give an even coverage.</p>	<p>4.0</p> <p>For chips and deep scratches, use fine wet &amp; dry paper to smooth out. Remove any dust from the area with a clean dry brush.</p> <p>Follow steps 2 or 3 to cover the damaged area.</p> <p>Observe the paint manufacturers product information sheet for health and safety advice.</p> <p>Citysquared always recommend suitable protective clothing and gloves are worn.</p>